

## F-1000 BT

MODELLO	F-1000BT
Enclosure	Bass reflex type
Rated Input	10 W (High Impedance)
Power Handling Capacity	Continuous pink noise: 30 W (low impedance) Continuous program: 90 W (low impedance)
Impedance	8 $\Omega$ 100 V line: 670 $\Omega$ (15 W), 2 k $\Omega$ (5 W), 3.3 k $\Omega$ (3 W), 10 k $\Omega$ (1 W) 70 V line: 330 $\Omega$ (15 W), 670 $\Omega$ (7.5 W), 2 k $\Omega$ (2.5 W), 3.3 k $\Omega$ (1.5 W), 10 k $\Omega$ (0.5 W)
Sensitivity	87 dB (1 W, 1 m) at installation in 1/2 free sound field
Frequency Response	85 Hz - 20 kHz, -10 dB at installation in 1/2 free sound field
Crossover Frequency	5 kHz
Directivity Angle	Horizontal: 90° , Vertical: 90°
Speaker Component	Low frequency: 10 cm (4") cone-type High frequency: Balanced dome tweeter
Input Terminal	Push-in terminal
Finish	Enclosure: HIPS, black Punched net: Surface-treated steel plate, black, paint Joint bracket, wall bracket: Steel plate, t1.6, black, paint Speaker bracket: Die-cast aluminum, black, paint
Dimensions	130 (W) x 202 (H) x 131 (D) mm (5.12" x 7.95" x 5.16")
Weight	2 kg (4.41 lb) (including the supplied brackets)
Accessory	Speaker bracket...1, Joint bracket...1, Wall bracket...1, Bracket fixing screw...1 set
Option	Board hanger bracket: HY-BH10B, Ceiling mount bracket: HY-CM10B (used for the horizontal speaker mounting), Cluster bracket: HY-CL10B, Speaker stand: ST-16A