

LG 55XE3C 55"

MODELLI	55XE3C 55"
Screen Size	55" Class (54.64" measured diagonal)
Brightness(Typ., with Protective Glass, cd/m²)	3000
Native Resolution	1,920 x 1,080 (FHD), M+
Input	HDMI, DP, DVI-D, Audio
Output	DP, External Speaker (*waterproof speakers are mandatory for outdoor installation)
External Control	RS232C, RJ45, SD Card, USB 3.0
Bezel Width	66.4 mm (T/B), 31.0 mm (L/R)
Monitor Dimension (W × H × D)	745.3 x 1,345.4 x 160.0 mm
Weight (Head)	70 kg
Operation Temperature	-30 °C to 50 °C
Operation Humidity	5 % to 100 %
Power Supply	100-240V~, 50/60Hz
Power Type	Built-In Power
Safety	UL / cUL / CB
EMC	FCC Class *A* / CE / KCC
ErP / Energy Star	No / No
CPS type compatible	No
External Media Player Attachable	No
Content Management Software	SuperSign Premium
Control and Monitoring Software	SuperSign C
Basic	Remote controller, EIG, ESG, Regulation book, Phone to RS232C gender, USB cable, HDMI cable
Optional	Media player (driven by customer), Enclosure Stand (ST-550X)