

BREEZE SERIES

MODELLI	P1.9	P2.6	P2.9	P3.9
Pixel Pitch (mm)	1.953	2.604	2.976	3.906
Pixel Density (dot/m ²)	262,144	147,456	112,896	65,536
Module Size (mm)	250x250	250x250	250x250	250x250
Panel size (mm)	1000x250x53.17 / 750x250x53.17	1000x250x53.4 / 750x250x53.4	1000x250x53.3 / 750x250x53.3	1000x250x53.42 / 750x250x53.42
Panel Resolution (dot)	512x128 / 384x128	384x96 / 288x96	336x84 / 252x84	256x64 / 192x64
Panel Material	Die-casting alluminium	Die-casting alluminium	Die-casting alluminium	Die-casting alluminium
Panel weight (kg/pcs)	6.4/5	6.4/5	6.4/5	6.4/5
Brightness (cd/m ²)	800	1000	1000	1200
Horizaontal & Vertical viewing angle	160/140	160/140	160/140	160/140
Contrast ratio	4000:1	4000:1	4000:1	4000:1
Max. & Avg. Power Consumption (w/m ²)	680/225	640/210	640/210	640/210
Refresh Rate (HZ)	3840	3840	3840	3840
Maintenance Way	Front or Rear	Front or Rear	Front or Rear	Front or Rear
Installation Way	Front or Rear	Front or Rear	Front or Rear	Front or Rear
IP Rate	IP20	IP20	IP20	IP20
Certification	CE,RoHS,EMC,CCC	CE,RoHS,EMC,CCC	CE,RoHS,EMC,CCC	CE,RoHS,EMC,CCC