

# Transparent film LED

MODELLI	P3	P4	P5	P6	P7,625	P8	P10	P12
Pixel pitch	3mm	4mm	5mm	6mm	7,625mm	8mm	10mm	12mm
Diameter (customizable)	1,2m - 1,5m - 1,6m - 2m - 3m	1m - 1,8m - 2.2m - 2,5m	1m - 1,8m - 2.2m - 7,2m	1,5m - 1,8m - 4m - 4,2m - 6m	1,8m - 2m - 2,5m	3m	1m - 2m - 3m	4m
LED type	SMD2121 / SMD1515			SMD3528 / SMD2121				
Pixel density (px/m <sup>2</sup> )	111111	62500	40000	27777	17222	15625	10000	6944
Scan	1/24	1/16	1/16	1/16	1/8	1/8	1/4	1/4
Brightness	≥1220	1800	1500	1600	1500	1300	1800	1000
Aver.Power Consumption (W/m <sup>2</sup> )	≤290	≤280	≤260	≤170	≤220	≤180	≤240	≤190
Max power Consumption (W/m <sup>2</sup> )	≤900	≤780	≤520	≤650	≤430	≤370	≤480	≤380
Refresh rate	1920~3849 HZ							
Weight (Kg/m <sup>2</sup> )	≈36Kg/m <sup>2</sup>							
Weight (Kg/m <sup>2</sup> including package)	≈45Kg/m <sup>2</sup>							
Frame Refresh Frequency	>60 HZ							
Brightness level	256							