

27,5" LED PANEL

| MODELLI | P1.2 | P1.5 | P1.9 | P2.5 |
|--|---|---|---|---|
| Cabinet Resolution | 480x270 | 384x216 | 304,96x171,54 | 240x135 |
| Lamp Type | SMD1010 | SMD1010 | SMD1515 | SMD2121 |
| Cabinet Size | 610x343x58 | 610x343x58 | 610x343x58 | 610x343x58 |
| Pixels Calibrations | Standard color and brightness calibration | Standard color and brightness calibration | Standard color and brightness calibration | Standard color and brightness calibration |
| Brightness | 600~1200 | 600~1200 | ≤ 1200 (max 3500 nits) | 600~1200 |
| Gray scale | 10~24 | 10~24 | 10~24 | 10~24 |
| Color temp [K] | 2500 - 9000 | 2500 - 9000 | 2500 - 9000 | 2500 - 9000 |
| Control system | VOD synchronous Color System | VOD synchronous Color System | VOD synchronous Color System | VOD synchronous Color System |
| Frame frequency | 60Hz - 120Hz | 60Hz - 120Hz | 60Hz - 120Hz | 60Hz - 120Hz |
| Refresh rate | ≤3840 Hz | ≤3840 Hz | ≤3840 Hz | ≤3840 Hz |
| Working Voltage | 100V~240V 50~60Hz | 100V~240V 50~60Hz | 100V~240V 50~60Hz | 100V~240V 50~60Hz |
| Power consumption (Peak Power) [w/m ²] | ≤800 | ≤715 | ≤590 | ≤355 |
| Power consumption (Average) [w/m ²] | ≤560 | ≤500 | ≤410 | ≤250 |
| Lifetime (h) | 1000.000 | 1000.000 | 1000.000 | 1000.000 |
| Operating Temp | -10°C - 60°C | -10°C - 60°C | -10°C - 60°C | -10°C - 60°C |
| Storage Temp | -25°C - 60°C | -25°C - 60°C | -25°C - 60°C | -25°C - 60°C |
| Humidity Range | 10% - 90% | 10% - 90% | 10% - 90% | 10% - 90% |
| Weight [kg] | 6.3 | 6.3 | 6.3 | 6.3 |